



Hanger-Saddle Combo

Featuring Buckaroos unique New Round Cornered "Roundup Saddle"



Product Overview

The Hanger-Saddle Combo from Buckaroos offers protection to the vapor barrier that encapsulates the pipe and a durable means of supporting overhead piping, ranging in size from 2" O.D. to 12" O.D. The product is composed of a galvanized shield that rests in a centered position inside a galvanized clevis hanger. The two components are spot-welded together at the point of contact. Depending on the application, the Hanger-Saddle Combo is available in galvanized carbon steel or in stainless steel.

The Hanger-Saddle Combo is designed especially to protect the integrity of the jacketing on insulated piping systems. However, it can also be used with non-insulated piping systems.



9635 Park Davis Drive
Indianapolis, IN 46235
1-800-969-3113
T: 317-899-9100
F: 317-899-0775

It's all about Safety!

Features and Benefits

- **Safety** — The one-piece design of the Hanger-Saddle Combo minimizes the opportunity for the shield to fall from the hanger location.
- **Round Corner Design** — The Hanger-Saddle Combo is the only product of its kind that does not have sharp, pointed corners. Installers are able to handle the product without the fear of cutting themselves.
- **O.D. Size marked on each saddle** — Provides easy identification in the warehouse or on job sites.
- **Vapor Barrier Protection** — The round corner design protects the insulation jacketing from being penetrated by the sharp corners on traditional insulation shields during installation. It also protects during the life of the piping system. If the system is subject to expansion, contraction or movement due to water hammer, the corners will not be forced through the jacketing.
- **All-in-One Solution** — The hanger and saddle are shipped to the end user as a single unit. This eliminates the problem of matching the correct shield and hanger sizes on the job site and dedicating valuable time to determining sizes that are compatible from differing manufacturers.

Sizes Available

Saddle I.D. (inches)	Nominal O.D. (inches)	Hanger Size (inches)	Rod Size (inches)	Saddle Length (inches)	Saddle Gauge
1.90	2.0	1 1/2	3/8	8,12	22
2.38	2.5	2	3/8	8,12	22
2.88	3.0	2 1/2	1/2	8,12	22
3.50	3.5	3	1/2	8,12	22
4.00	4.0	3 1/2	1/2	8,12	22
4.50	4.5	4	5/8	8,12	22
5.00	5.0	5	5/8	8,12	22
5.63	5.5	5	5/8	8,12	22
6.13	6.0	6	3/4	12	20
6.64	6.5	6	3/4	12	20
7.64	7.5	8	3/4	12	20
8.64	8.5	8	3/4	12	20
9.64	9.5	10	7/8	12	20
11.0	11.00	10	7/8	12	20
12.0	12.00	12	7/8	12	20

Notes:

- (1) Always refer to your project specification for saddle length and gauge requirements.
- (2) Individual project requirements may vary considerably from the chart.
- (3) Buckaroos can provide virtually any saddle length and gauge combination upon request.